

38<AN・MS SCREWS>AN・MSネジ関係

☆MS35206 MACHINE SCREWS (AN515)

(60000 psi minimum tensile strength)

商品番号	Thread Size	LENGTH インチ(ミリ)	価格 1本	商品番号	Thread Size	LENGTH インチ(ミリ)	価格 1本
MS35206-203	2-56	1/4(6.35)	¥30	MS35206-241	8-32	1/4(6.35)	¥60
MS35206-204		5/16(7.94)	¥40	MS35206-242		5/16(7.94)	
MS35206-205		3/8(9.53)	¥30	MS35206-243		3/8(9.53)	
MS35206-206		7/16(11.11)	¥40	MS35206-244		7/16(11.11)	
MS35206-207		1/2(12.70)		MS35206-245		1/2(12.70)	
MS35206-208		5/8(15.88)		MS35206-246		5/8(15.88)	
MS35206-209		3/4(19.05)	¥50	MS35206-247		3/4(19.05)	
MS35206-212		3/16(4.76)		MS35206-248		7/8(22.23)	
MS35206-213		1/4(6.35)		¥30		MS35206-249	
MS35206-214	5/16(7.94)	¥40		MS35206-250	1-1/4(31.75)		
MS35206-215	3/8(9.53)			MS35206-251	1-1/2(38.10)		
MS35206-216	7/16(11.11)			¥30	MS35206-252	1-3/4(44.45)	
MS35206-217	1/2(12.70)	¥50		MS35206-253	2(50.80)		
MS35206-218	5/8(15.88)			MS35206-261	3/8(9.53)		
MS35206-219	3/4(19.05)			¥50	MS35206-262	7/16(11.11)	
MS35206-220	7/8(22.23)	¥60		MS35206-263	1/2(12.70)		
MS35206-221	1(25.40)			MS35206-264	5/8(15.88)		
MS35206-222	1-1/4(31.75)			MS35206-265	3/4(19.05)		
MS35206-223	1-1/2(38.10)	¥50	MC35206-267	1(25.40)			
MS35206-226	1/4(6.35)		MS35206-279	1/2(12.70)			
MS35206-227	5/16(7.94)		¥60	MS35206-280	5/8(15.88)		
MS35206-228	3/8(9.53)			MS35206-281	3/4(19.05)		
MS35206-229	7/16(11.11)			¥60			
MS35206-230	1/2(12.70)						
MS35206-231	5/8(15.88)						
MS35206-232	3/4(19.05)						
MS35206-233	7/8(22.23)						
MS35206-234	1(25.40)						
MS35206-235	1-1/4(31.75)						
MS35206-236	1-1/2(38.10)						
MS35206-238	2(50.80)						

Phillips head




☆MS24693 MACHINE SCREWS (AN507)

(55000 psi minimum tensile strength)

商品番号	Thread Size	LENGTH インチ(ミリ)	価格 1本	商品番号	Thread Size	LENGTH インチ(ミリ)	価格 1本		
MS24693-S17	2-56	5/32(3.97)	¥220	MS24693-C4	4-40	3/8(9.53)	¥30		
MS24693-S4		3/8(9.53)	¥40	MS24693-C5		7/16(11.11)	¥40		
MS24693-S5		7/16(11.11)	¥30	MS24693-C6		1/2(12.70)	¥30		
MS24693-S6		1/2(12.70)	¥40	MS24693-C7		5/8(15.88)	¥40		
MS24693-S7		5/8(15.88)		MS24693-C10		1(25.40)	¥50		
MS24693-S10		1(25.40)		¥50		MS24693-C24	1/4(6.35)	¥30	
MS24693-S24	6-32	1/4(6.35)	¥40	MS24693-C26	3/8(9.53)	¥40			
MS24693-S26		3/8(9.53)		MS24693-C27	7/16(11.11)				
MS24693-S28		1/2(12.70)		MS24693-C28	1/2(12.70)				
MS24693-S29		5/8(15.88)	¥50	MS24693-C30	3/4(19.05)	¥50			
MS24693-S30		3/4(19.05)		MS24693-C32	1(25.40)				
MS24693-S32		1(25.40)		¥50	MS24693-C46		1/4(6.35)	¥60	
MS24693-S34		1-1/4(31.75)	¥60	MS24693-C48	3/8(9.53)				
MS24693-S36		1-1/2(38.10)	¥110	MS24693-C49	7/16(11.11)				
MS24693-S46		8-32	1/4(6.35)	¥40	MS24693-C50	1/2(12.70)	¥70		
MS24693-S48			3/8(9.53)	¥50	MS24693-C51	5/8(15.88)			¥90
MS24693-S50			1/2(12.70)		MS24693-C52	3/4(19.05)			
MS24693-S51			5/8(15.88)		¥40	MS24693-C54			
MS24693-S52	3/4(19.05)		¥60	MS24693-C56	1-1/4(31.75)	¥110			
MS24693-S54	1(25.40)			MS24693-C268	1/4(6.35)	¥80			
MS24693-S56	1-1/4(31.75)	¥70		MS24693-C270	3/8(9.53)	¥60			
MS24693-S66	10-32	3/16(4.76)	¥90	MS24693-C271	7/16(11.11)	¥70			
MS24693-S268		1/4(6.35)	¥50	MS24693-C272	1/2(12.70)	¥80			
MS24693-S270		3/8(9.53)		MS24693-C273	5/8(15.88)	¥90			
MS24693-S272		1/2(12.70)		¥70	MS24693-C274	3/4(19.05)	¥120		
MS24693-S273		5/8(15.88)	¥60	MS24693-C276	1(25.40)				
MS24693-S274		3/4(19.05)	¥70	MS24693-C278	1-1/4(31.75)	¥140			
MS24693-S276		1(25.40)	¥90	MS24693-C293	7/16(11.11)	¥130			
MS24693-S277		1-1/8(28.57)	¥120	MS24693-C294	1/2(12.70)	¥140			
MS24693-S278		1-1/4(31.75)	¥90	MS24693-C295	5/8(15.88)	¥120			
MS24693-S286		1/4-28	3/8(9.53)	¥225	MS24693-C298	1(25.40)	¥200		
MS24693-S294			1/2(12.70)	¥100	MS24693-BB10	4-40	1(25.40)	¥560	
MS24693-S295			5/8(15.88)	¥120					
MS24693-S298	1(25.40)								
MS24693-S306	2(50.80)		¥360						


Phillips head



38<AN・MS SCREWS>AN・MSネジ関係

38 AN525 WASHER HEAD SCREWS

(125000 psi tensile strength)



商品番号	Thread Size	LENGTH インチ(ミリ)	GRIP インチ(ミリ)	価格 (1本)
AN525-832R5	8-32	5/16(7.94)		¥60
AN525-832R6		3/8(9.53)	1/32(0.79)	
AN525-832R7		7/16(11.11)	1/16(1.59)	
AN525-832R8		1/2(12.70)	1/8(3.18)	
AN525-832R9		9/16(14.28)	1/8(3.18)	
AN525-832R10		5/8(15.88)	7/32(5.56)	
AN525-832R11		11/16(17.46)	9/32(7.14)	
AN525-832R12		3/4(19.05)	11/32(8.73)	
AN525-832R14		7/8(22.23)	15/32(11.91)	
AN525-832R16		1(25.40)	19/32(15.08)	
AN525-832R18		1-1/8(28.57)	23/32(18.26)	
AN525-832R20		1-1/4(31.75)	27/32(21.43)	
AN525-832R22	1-3/8(34.92)	31/32(24.60)		
AN525-832R24	1-1/2(38.10)	1-3/32(27.78)		
AN525-8R9	8-36	9/16(14.28)	5/32(39.68)	¥80
AN525-10R4	10-32	1/4(6.35)		¥90
AN525-10R5		5/16(7.94)		
AN525-10R6		3/8(9.53)	1/32(0.79)	
AN525-10R7		7/16(11.11)	1/16(1.59)	
AN525-10R8		1/2(12.70)	1/8(3.18)	
AN525-10R9		9/16(14.28)	5/32(3.97)	
AN525-10R10		5/8(15.88)	7/32(5.56)	
AN525-10R12		3/4(19.05)	11/32(8.73)	
AN525-10R14		7/8(22.23)	15/32(11.91)	
AN525-10R16		1(25.40)	19/32(15.08)	
AN525-10R18		1-1/8(28.57)	23/32(18.26)	
AN525-10R20		1-1/4(31.75)	27/32(21.43)	
AN525-10R24	1-1/2(38.10)	1-3/32(27.79)		
AN525-416R6	1/4-28	3/8(9.53)	1/32(0.79)	¥150
AN525-416R7		7/16(11.11)	1/16(1.59)	
AN525-416R8		1/2(12.70)	1/8(3.18)	
AN525-416R9		9/16(14.28)	5/32(3.97)	
AN525-416R10		5/8(15.88)	7/32(5.56)	
AN525-416R12		3/4(19.05)	11/32(8.73)	
AN525-416R14		7/8(22.23)	15/32(11.91)	
AN525-416R16		1(25.40)	19/32(15.08)	
AN525-416R20		1-1/8(28.57)	27/32(21.43)	
AN525-416R30		1-1/4(31.75)	1-15/32(37.31)	

32 AN365 NYLON-INSERT

(ナイロンロックナット)

AN365/MS21044/NAS1021N

商品番号	Thread Size	価格	備考
32-AN365-632A	6-32	¥40	
32-AN365-832A	8-32	¥40	
32-AN365-1032A	10-32	¥40	AN3用
32-AN365-428A	1/4-28	¥50	AN4用




※これらは一般的なナイロンロックナットです。

38 BRASS INSTRUMENT SCREWS

(PIN HEND (+) 計器取付用 BRASS

(真鍮製ネジ)

商品番号	Thread Size	LENGTH インチ(ミリ)	価格 1本	
MS35214-12	4-40	1/4(6.35)	¥70	
MS35214-13		5/16(7.94)		
MS35214-14		3/8(9.53)		
MS35214-15		7/16(11.11)		
MS35214-16		1/2(12.70)		
MS35214-18		3/4(19.05)		
MS35214-23	6-32	1/4(6.35)	80	
MS35214-24		5/16(7.94)		
MS35214-25		3/8(9.53)		
MS35214-26		7/16(11.11)		
MS35214-27		1/2(12.70)		
MS35214-28		5/8(15.88)		
MS35214-29		3/4(19.05)		
MS35214-30		7/8(22.23)		
MS35214-31		1(25.40)		
MS35214-32		1-1/4(31.75)		90
MS35214-33		1-1/2(38.10)		
MS35214-40		3/8(9.53)		
MS35214-41	7/16(11.11)			
MS35214-42	1/2(12.70)			
MS35214-43	5/8(15.88)			
MS35214-44	3/4(19.05)			
MS35214-45	7/8(22.23)			
MS35214-46	1(25.40)			
MS35214-47	1-1/4(31.75)			
MS35214-48	1-1/2(38.10)			
MS35214-59	10-24	1(25.40)	190	



38 NAS8703 GA SCREWS



商品番号	Finish	Thread Size	GRIP インチ	LENGTH インチ	価格 (1本)
NAS8703-2	Cadmium Per Ams QQ-P-416 TYPE II	10-32	0.125	0.448	¥550
NAS8703-3			0.187	0.511	¥630
NAS8703-4			0.250	0.573	¥200
NAS8703U2	Passivate Per Ams 2700	10-32	0.125	0.448	¥240
NAS8703U3			0.187	0.511	
NAS8703U4			0.250	0.573	
NAS8703U5			0.312	0.635	
NAS8703U5			0.312	0.635	

32 INSTRUMENT MOUNTING NUTS

(計器取付用ナット)

商品番号	NAS 商品番号	厚さ	価格
A8938-632-493	487.13	.062	¥350
A8939-632-493	487.14	.091	
A8939-632-493	487.15	.125	
A8940-632-493	487.16	.187	
A8941-632-493	487.17	.250	
A8942-632-493	487.18	.313	
A8943-632-493	487.20	.375	
A8944-632-493	487.21	.375	



※航法及びエンジン計器を固定する為のワンタッチ式ナットです。真鍮製ですので、磁気に影響されませんので、コンパスを始めとするあらゆる計器にご使用下さい。取付計器及びパネル等の厚みにより上記より選んで下さい。375”(9.52mm)以上の場合、A8944-632-493を選んで下さい。取付ネジは全て6-32です。

38 AN526 MACHINE SCREWS (55000 psi minimum tensile strength)

☆スチール製

商品番号	Thread Size	LENGTH インチ(ミリ)	価格(1本)		
			Phillips ⊕	Slotted ⊖	
AN526-440R4	4-40	1/4(6.35)	¥60	-	
AN526-440R6		3/8(9.53)	¥50	-	
AN526-440R8		1/2(12.70)	-	-	
AN526-632R4	6-32	1/4(6.35)	-	-	
AN526-632R5		5/16(7.94)	-	-	
AN526-632R6		3/8(9.53)	¥60	-	
AN526-632R7		7/16(11.11)	-	-	
AN526-632R8		1/2(12.70)	¥60	-	
AN526-632R9		9/16(14.29)	¥50	-	
AN526-632R10		5/8(15.88)	¥100	-	
AN526-632R12		3/4(19.05)	¥50	-	
AN526-632R14		7/8(22.23)	-	-	
AN526-632R16		1(25.4)	¥80	-	
AN526-632R18	1-1/8(28.58)	¥50	-		
AN526-632R20	1-1/4(31.75)	¥80	-		
AN526-632R24	1-1/2(38.1)	¥60	-		
AN526-632R32	2(50.8)	-	-		
AN526-832R4	8-32	1/4(6.35)	-	-	
AN526-832R5		5/16(7.94)	-	-	
AN526-832R6		3/8(9.53)	-	-	
AN526-832R7		7/16(11.11)	-	-	
AN526-832R8		1/2(12.70)	¥50	¥100	
AN526-832R9		9/16(14.29)	-	-	
AN526-832R10		5/8(15.88)	-	-	
AN526-832R12		3/4(19.05)	¥80	-	
AN526-832R14		7/8(22.23)	-	-	
AN526-832R16		1(25.4)	¥60	¥60	
AN526-832R18		1-1/8(28.58)	¥60	¥50	
AN526-832R20		1-1/4(31.75)	¥80	-	
AN526-832R24		1-1/2(38.1)	¥80	-	
AN526-832R28		1-3/4(44.45)	-	¥80	
AN526-1032R4		10-32	1/4(6.35)	¥60	-
AN526-1032R5			5/16(7.94)	-	-
AN526-1032R6			3/8(9.53)	-	-
AN526-1032R7			7/16(11.11)	¥50	-
AN526-1032R8	1/2(12.70)		¥100	-	
AN526-1032R9	9/16(14.29)		-	-	
AN526-1032R10	5/8(15.88)		-	¥60	
AN526-1032R12	3/4(19.05)		-	-	
AN526-1032R14	7/8(22.23)		-	-	
AN526-1032R16	1(25.4)		¥60	¥80	
AN526-1032R18	1-1/8(28.58)		-	¥60	
AN526-1032R20	1-1/4(31.75)		-	-	
AN526-1032R30	1-7/8(47.63)		-	¥60	
AN526-1032R32	2(50.8)		¥100	-	

☆ステンレス製

商品番号	Thread Size	LENGTH インチ(ミリ)	価格(1本)	
			Phillips ⊕	Slotted ⊖
AN526C-440R8	4-40	1/2(12.70)	¥50	-
AN526C-632R4	6-32	1/4(6.35)	-	¥80
AN526C-632R6		3/8(9.53)	-	-
AN526C-632R8		1/2(12.70)	¥50	¥60
AN526C-632R10		5/8(15.88)	-	-
AN526C-632R12		3/4(19.05)	-	¥80
AN526C-632R16	1(25.4)	-	-	
AN526C-832R4	8-32	1/4(6.35)	¥60	-
AN526C-832R6		3/8(9.53)	-	-
AN526C-832R8		1/2(12.70)	¥50	¥60
AN526C-832R10		5/8(15.88)	-	¥80
AN526C-832R12		3/4(19.05)	-	-
AN526C-832R16		1(25.4)	¥60	¥60
AN526C-1032R4	10-32	1/4(6.35)	¥80	-
AN526C-1032R6		3/8(9.53)	-	¥80
AN526C-1032R8		1/2(12.70)	-	-
AN526C-1032R10		5/8(15.88)	¥60	¥60
AN526C-1032R12		3/4(19.05)	-	-
AN526C-1032R16		1(25.4)	-	¥80
AN526C-1032R24		1-1/2(38.1)	¥80	-
AN526C-420R8		1/4-20	1/2(12.70)	¥280
AN526C-428R8	1/4-28	1/2(12.70)	¥80	-
AN526C-428R12		3/4(19.05)	¥100	-



38 MS35207 MACHINE SCREWS (AN520) (55000 psi minimum tensile strength)

商品番号	Thread Size	LENGTH インチ(ミリ)	価格 (1本)
MS35207-260	10-32	5/16(7.94)	¥60
MS35207-261		3/8(9.53)	
MS35207-262		7/16(11.11)	
MS35207-263		1/2(12.70)	
MS35207-264		5/8(15.88)	
MS35207-265		3/4(19.05)	
MS35207-266		7/8(22.23)	
MS35207-267		1(25.40)	
MS35207-268		1-1/4(31.75)	
MS35207-269		1-1/2(38.10)	
MS35207-270		1-3/4(44.45)	
MS35207-271		2(50.80)	

Phillips head



TEL 022-394-7788 MAIL : info@skylife.co.jp
FAX 022-394-7787 http://www.skylife.co.jp